

**TECHNICAL UNIVERSITY OF CLUJ-NAPOCA** 

**ACTA TECHNICA NAPOCENSIS** 

Series: Applied Mathematics and Mechanics Vol. 55, Issue II, 2012

# SOLVING DYNAMIC MODELLING OF TTRT GANTRY MODULAR ROBOT BY NEWTON EULER FORMALISM

## Adrian Vasile BLEBEA, Viorel ISPAS, Radu Mircea MORARIU-GLIGOR, Iosif Nicuşor URSA

Abstract. Dynamic equations of a robot shall be determined by an iterative method. This method highlights the generalized variables: generalized driving forces and liaison forces that appear in the components of the robot. So, knowing the position vectors of the centers of masses, the work aims to determine the accelerations associated with mass centres, the external forces and moments torsor, the liaison forces and moments torsor, respectively generalized drivinf forces of a Gantry modular robot. In this paper the authors present the dynamic modeling of a 4 d.o.f. Gantry robotic structure, type TTRT.

Key words: kinematics model, dynamic model, modular robot, Gantry structure.

#### **1. INTRODUCTION**

The dynamic equations of a robot are determined by an iterative method, which emphasizes the generalized variables, the driving generalized forces and the contact forces that arise between linked components of the robot. The calculation algorithm is based on the Luth-Walker-Paul method [3] and consists of the two iteration to the mechanical structure for the parts robot, respectively:

- Iterations to the exterior structure,

-Iterations inside the structure.

#### 2. THEORETICAL JUSTIFICATION

In accordance with the kinematics structure of a robot with n degrees of freedom (fig.1), it can be established the dynamic equations of a robot [1]. The kinematics structure of the robot it's geometric modeling, thus, for each item i is determined the homogeneous transformation matrix:

$$[T]_{i}^{i-1} = \begin{bmatrix} [R]_{i}^{i-1} & | & [\bar{r}]_{i}^{i-1} \\ --- & | & --- \\ 0 & 0 & 0 & | & 1 \end{bmatrix}$$
(1)

If the method of compounds operators DH in the second variant is applied, the matrix elements (1) following meanings:

 $[R]_{i}^{i-1}$  is the rotation matrix defining the orientation of each axis of the system (T<sub>i</sub>) with the system (T<sub>i-1</sub>) and has the expression:

$$[R]_{i}^{i-1} = \begin{bmatrix} c\theta_{i} & -s\theta_{i} & 0\\ s\theta_{i}c\alpha_{i-1} & c\theta_{i}c\alpha_{i-1} & -s\alpha_{i-1}\\ s\theta_{i}s\alpha_{i-1} & c\theta_{i}s\alpha_{i-1} & c\alpha_{i-1} \end{bmatrix}$$
(2)

 $\overline{r_i^{i^{-1}}}$  is the column vector which defines the position of origin  $O_i$  of the system (T<sub>i</sub>) in relation with the origin  $O_{i+1}$  of the system (T<sub>i+1</sub>), with the matrix expression:

$$[\bar{r}]_{i}^{i-1} = [a_{i} - d_{i}s\alpha_{i-1} \ d_{i}c\alpha_{i-1}]^{T}.$$
(3)

It's determine the inverse rotation matrix  $[R]_i^{i-1}$ :

$$[R]_{i-1}^{i} = [R_{i-1}^{i}]^{-1} = [R_{i-1}^{i}]^{T}, \text{ and hence,}$$

$$[R]_{i-1}^{i} = \begin{bmatrix} c\theta_{i} & s\theta_{i}c\alpha_{i-1} & s\theta_{i}s\alpha_{i-1} \\ -s\theta_{i} & c\theta_{i}c\alpha_{i-1} & c\theta_{i}s\alpha_{i-1} \\ 0 & -s\alpha_{i-1} & c\alpha_{i-1} \end{bmatrix}.$$
(4)

For each item i are determined the following parameters:

 $M_i$  – the mass of the element i of a robot with n degrees of freedom

$$M_i = \sum_{j=1}^{k_i} \sigma_j m_j$$
, in witch

 $\sigma_j = +1$  if the item j remains in the item i composition;  $\sigma_j = -1$  if the item j is eliminated;

 $\bar{r}_{c_i}^i$  - the position vector of the mass center  $C_i$  in relation with the origin  $O_i$  of the reference system ( $T_i$ ), with the relation:

$$\begin{bmatrix} \bar{r}_c \end{bmatrix}_i^{iD} = \begin{bmatrix} T \end{bmatrix}_i^{iD} \cdot \begin{bmatrix} \bar{r}_c \end{bmatrix}_i^i = \begin{bmatrix} x_{c_i}^{iD} & y_{c_i}^{iD} & z_{c_i}^{iD} & 1 \end{bmatrix}^T,$$
(5)

where  $[T_{j}^{\mu\nu}]$  is the matrix that defines the position and the orientation of each axis of the reference system (T<sub>i</sub>) in relation to the reference system DH, (T<sub>iD</sub>) which can be determined, according to [5] the relation:

$$[T]_{i}^{iD} = \begin{bmatrix} \bar{\mathbf{x}}_{iD}^{T} \\ \bar{\mathbf{y}}_{iD}^{T} \\ \bar{\mathbf{z}}_{iD}^{T} \end{bmatrix} \cdot \begin{bmatrix} \bar{\mathbf{x}}_{i} \ \bar{\mathbf{y}}_{i} \ \bar{\mathbf{z}}_{i} \end{bmatrix} \begin{vmatrix} \bar{\mathbf{x}}_{iD}^{T} (\bar{p}_{i} - \bar{p}_{iD}) \\ \bar{\mathbf{y}}_{iD}^{T} (\bar{p}_{i} - \bar{p}_{iD}) \\ \bar{\mathbf{z}}_{iD}^{T} \end{bmatrix} \cdot \begin{bmatrix} \bar{\mathbf{x}}_{i} \ \bar{\mathbf{y}}_{i} \ \bar{\mathbf{z}}_{iD} \\ \bar{\mathbf{z}}_{iD}^{T} (\bar{p}_{i} - \bar{p}_{iD}) \\ \bar{\mathbf{z}}_{iD} \end{bmatrix} ;$$
(6)

 $J_i^{*i}$  – the inertial tensor of the element i compared with the reference system ( $T_i^*$ ) with the origin in the mass center  $C_i$ . This is determined according to [Isp 04], with the following relation:

$$J_{i}^{*iD} = \begin{bmatrix} J_{x}^{*iD} & -J_{xy}^{*iD} & -J_{xz}^{*iD} \\ -J_{yx}^{*iD} & J_{y}^{*iD} & -J_{yz}^{*iD} \\ -J_{zx}^{*iD} & J_{zy}^{*iD} & J_{z}^{*iD} \end{bmatrix}$$
(7)

where the matrix elements are the axial and centrifugal mechanical moments of inertia of the element i determined in relation with the reference system  $(T_{iD})$ , with the origin in the mass center  $C_i$ .

On the robot acts the system of the weight forces for every element i  $(i=1\div n)$  and a system of external forces situated at the end of the robot.

The system of external forces is reduced compared to the origin  $O_{n+1}$  of the reference system  $(T_{n+1})$ , jointly with the gripper and the manipulated object caught in the grip handle. Thus, it's obtain the reduction torsos of the external forces, with the elements: the resultant force  $\overline{F}_{n+1}^{n+1}$  and the resultant moment  $\overline{M}_{O_{n+1}}^{n+1}$ , expressed in the reference system  $(T_{n+1})$ . If the robot is in motion, then on each axis of motion the generalized variables  $q_i, \dot{q}_i, \dot{q}_i, i = 1 \div n$  are highlighted. The kinematic parameters that characterize the movement of the element I, at a time, are  $\overline{\omega}_i^i, \overline{\varepsilon}_i^i, \overline{v}_{c_i}, \overline{a}_{c_i}, i = 1 \div n$ , which are added the kinematics parameters of the fixed element (0):

$$\begin{bmatrix} \overline{\omega} \end{bmatrix}_{0}^{0} = \begin{bmatrix} \dot{\overline{\omega}} \end{bmatrix}_{0}^{0} = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^{T} \\ \begin{bmatrix} \dot{\overline{v}} \end{bmatrix}_{0}^{0} = \begin{bmatrix} 0 & 0 & g \end{bmatrix}^{T},$$
(8)

where g is the gravitational acceleration.

By applying the Newton-Euler method the robot's dynamic equations are determined, from which are obtained the generalized driving forces.  $Q_m^{'}$ . These results are obtained covering the two stages of the calculation algorithm and by introducing the notation:

$$\begin{cases} \Delta_i = 1, \text{ in the case of rotation } (i=1 \div n) \\ \Delta_i = 0, \text{ in the case of translation} \end{cases}$$
(9)

# 1) <u>Iterations to the exterior of the</u> robot mechanical structure.

Using the Newton-Euler dynamic equations, is determined for each element i,  $(i=1\div n)$ , component of the robot, the linear and angular velocities and accelerations, the forces and moments exterior forces.

Applying the calculation algorithm of the iterative method presented in the kinematics modeling, [2] and [8] determine the following kinematics parameters:

 $\overline{\omega}_i^{i}$  - the angular velocity of the element i relative to the fixed system (T<sub>0</sub>) from the base of the robot, expressed in the system (T<sub>i</sub>) with the relation:

$$\overline{\omega}_{i}^{i} = \left[R\right]_{i-1}^{i} \cdot \overline{\omega}_{i-1}^{i-1} + \Delta_{i} \dot{q}_{i} \overline{k}_{i}^{i}; \tag{10}$$

 $\overline{\varepsilon}_i^i$  - the angular acceleration of the element i relative to the system (T<sub>0</sub>), expressed in the system (T<sub>i</sub>) with the relation:

$$\overline{\varepsilon}_{i}^{i} = \left[R\right]_{i-1}^{i} \cdot \overline{\varepsilon}_{i-1}^{i-1} + \Delta_{i} \left\{ \left[R\right]_{i-1}^{i} \overline{\omega}_{i-1}^{i-1} \times \dot{q}_{i} \overline{k}_{i}^{i} + \ddot{q}_{i} \overline{k}_{i}^{i} \right\};$$
(11)

 $\overline{a}_i^i$  - the linear acceleration of the origin of system (T<sub>i</sub>) relative to the fixed system (T<sub>0</sub>), expressed in the system (T<sub>i</sub>) with the relation:

$$\overline{a}_{i}^{i} = [R]_{i-1}^{i} \begin{cases} \overline{a}_{i-1}^{i-1} + \overline{\varepsilon}_{i-1}^{i-1} \times \overline{r}_{i}^{i-1} + \overline{\omega}_{i-1}^{i-1} \\ \times (\overline{\omega}_{i-1}^{i-1} \times \overline{r}_{i}^{i-1}) \end{cases} + \\ (1 - \Delta_{i}) (2\overline{\omega}_{i}^{i} \times \dot{q}_{i} \overline{k}_{i}^{i} + \ddot{q}_{i} \overline{k}_{i}^{i}); \qquad (12)$$

 $\overline{a}_{ci}$  - the mass center acceleration C<sub>i</sub> of the element i, determined in relation to the fixed system (T<sub>0</sub>) and expressed relative to the system (T<sub>i</sub>), by the relation:

$$\overline{a}_{c_i}^i = \overline{a}_i^i + \overline{\varepsilon}_i^i \times \overline{r}_{c_i}^i + \overline{\omega}_i^i \times \left(\overline{\omega}_i^i \times \overline{r}_{c_i}^i\right).$$
(13)



Fig. 1. The kinematic structure of a robot with n degrees of freedom

By applying to each element i, the dynamic equations of the Newton-Euler are obtained the reduction torsos elements for the external forces with the following expressions:

$$\overline{R}_{i}^{i} = M_{i}\overline{a}_{c_{i}}^{i} 
\overline{M}_{c_{i}}^{i} = J_{i}^{*i}\overline{\varepsilon}_{i}^{i} + \overline{\omega}_{i}^{i} \times J_{i}^{*i}\overline{\omega}_{i}^{i} .$$
(14)

# 2) <u>Iterations inside of the robot</u> mechanical structure.

Under this case, is determined for each element i,  $(i=1\div n)$ , of the robot, the forces torsos between the elements i, i+1, respectively the generalized driving forces of kinematics axes.

For each element i, it can be determined the reduction torsos of the contact forces. The elements of this torsos have the expressions:

$$\overline{F}_{l_{i}}^{i} = M_{i}\overline{a}_{c_{i}} - \overline{F}_{i}^{i} - [R]_{i+1}^{i}\overline{F}_{l_{i+1}}^{i+1} 
\overline{M}_{l_{o_{i}}}^{i} = \overline{r}_{c_{i}} \times M_{i}\overline{a}_{c_{i}} + J_{i}^{*}\overline{\varepsilon}_{i} + \overline{\omega}_{i} \times J_{i}^{*}\overline{\omega}_{i} - \overline{M}_{c_{i}}^{i} - 
\overline{r}_{c_{i}} \times \overline{F}_{i}^{i} - [R]_{i+1}^{i}\overline{M}_{l_{o_{i+1}}}^{i+1} - \overline{r}_{i+1}^{i} \times [R]_{i+1}^{i}\overline{F}_{l_{i+1}}^{i+1}.$$
(15)

From above relation, by transforming vectors  $\overline{E}^{i}$   $\overline{M}^{i}$ 

and the generalized driving forces  $Q_m^i$ , which actually represents the dynamic model of the robot:

$$\mathcal{Q}_m^i = \Delta_i \left[ M_{l_{Q_i}}^i \right]^T \cdot \overline{k}_i^i + \left( 1 - \Delta_i \right) \left[ \overline{F}_{l_i}^i \right]^T \cdot \overline{k}_i^i + \mathcal{Q}_f^i,$$
(17)

where  $Q_f^i$ , according to [8], reprezent the force caused by friction and has the expressions:  $Q_f^i = b_i \dot{a}_i + Q_f^i$ .

$$Q_{f}^{*} = b_{i}q_{i} + Q_{f_{c}}^{*}.$$
(18)

The parameters  $b_i$  și  $Q'_{f_c}$  from above relation represent:

b<sub>i</sub> – the viscous friction coefficient;

 $Q_{f_c}^{'}$  -the generalized force due to dry friction (Coulomb friction) and it has the expression:

$$Q_{f_c}^{i} = \Delta_i c_i \frac{d_i}{2} \left| \overline{k}_i^{i} \times \overline{F}_{l_i}^{i} \right| \operatorname{sgn} \dot{q}_i + (1 - \Delta_i) c_i \left| \overline{k}_i^{i} \times \overline{F}_{l_i}^{i} \right| \operatorname{sgn} \dot{q}_i.$$
(19)

In the above expression,  $c_i$  is the dry friction coefficient, and  $d_i$  is the diameter of spindle torque.

The dynamic equations system (17) can be written as:

$$\overline{Q}_m(t) = \left[Q_m^i(t) = f^{-1}(q_j(t), j = 1 \div n), i = 1 \div n\right]^T$$
(20)

and represents the dynamic model of the robot with n degrees of freedom.

In the direct problem of robot dynamics are known the column vector of the generalized driving forces. Thus, the functions can be deduced:

$$\overline{q}(t) = f\left\{\overline{Q}_m(t)\right\} = \left[q_i(t), i = 1 \div n\right]^T,$$
(21)

which is the robot law of motion in configurative states space. In the inverse problem of robot dynamics, called inverse dynamic model, functions  $\vec{q}(t)$  are known, and with the relation (17) the generalized driving forces  $\vec{Q}_m(t)$  are determinated [7].

Using Newton-Euler iterative method, with relation (15) can be determined the elements of contact forces torsor between the components of the robot. In conclusion, the Newton-Euler iterative method includes the following steps:

- It's shaped geometrical the mechanical structure of the robot with n degrees of freedom and are determined for each  $i=1\div n$ , the matrices (3) and their inverse.

Is calculated for each element i,  $i=1\div n$ , parameters which characterizing the mass distribution, namely: the mass  $M_i$ , the position vector  $\overline{r}_{c_i}^i$  of mass center C<sub>i</sub> relative with O<sub>i</sub> [7], [8] and the tensor  $J_i^{*i}$  with rel. (9).

It is calculated, by the iterations to the outside, the kinematics parameters (10)-(15) and the external forces torsor (16).

By iterations to the outside, are determined, the contact forces torsor, whose elements are given by (17), and the generalized driving forces using, the dynamic equations (19).

# The dynamic model of TTRT serial robot

The mechanical structural diagram of the TTRT industrial robot, shown in fugure 2 consists of: a traslation module 1 on the horizontal axis  $O_0y_1$ , the translation module 2 on the horizontal axis  $O_2x_2$ , the rotation module 3 of the vertical sled 4 on axis  $O_3z_3$  and the vertical sled 4 of the gripping device, witch executes a translation on axis  $O_4z_4$  [1].

The dynamic modeling of the TTRT robot, whose kinematics scheme is shown in figure 2 will be achieved by applying the Newton-Euler method, implemented in the symbolic modeling program *Robot Symbolic*, *Robot Dynamics module of the Matlab 7.1 program* [2].

For applying the method is required to develop the geometric and kinematics modeling, as well the determining of mass distribution parameters. On the basis of recommendations from the articles [4] and [6], it is noted:

 $l_1^i, l_i, i = 1 \div 4$  – constructive parameters of the robot  $i=1 \div 4$ 

 $\Delta_i$ ,  $i = 1 \div 4 - motion$  axis;

 $\Delta_5$  – parallel axis with axis  $\Delta_3$  of rotation of the arm, passing through the mass center C<sub>5</sub> of the gripping device;

 $q_k, \dot{q}_k, \ddot{q}_k$ , the generalized coordinates positions, velocities and accelerations

 $O_i$ ,  $i = 1 \div 4$  – origins of the systems  $O_i x_i y_i z_i$ , witch coincides with the mass centers of the robot modules;

O<sub>0</sub> – measurement base (zero point);

 $O_0 x_0 y_0 z_0$  – Cartesian reference fixed system

 $O_i x_i y_i z_i$  ,  $i=1{\div}4$  – Cartesian reference mobile system, solider with the mobile parts of the robot modules

 $\overline{G}_i$ ,  $i = 1 \div 5$  – the mass forces related to the modules respectively the gripping device.

 $\overline{F}_1$ ,  $\overline{F}_2$ ,  $\overline{F}_3$  - driving forces in the couplings 1. 2 and 3;

 $\overline{M}_3$ - the coupling torque 3;

 $m_i$ , i = 1.5 – all the masses including, modules and gripping device;

 $J_{z_3}^{(c)}$  - mechanical inertial moment of the module 3 in relation to the axis O<sub>3</sub> z<sub>3</sub>;

 $\mathrm{J}^{(4)}_{\Delta_4}$ 

 $\Delta_4$  - mechanical inertial moment of the mobile equipment of the orientation module 4 in relation to the axis  $\Delta_4$ .

It is also required some simplifying assumptions:

- It is considered the mass centers  $C_i$  located in in the origins  $O_i$  of the Cartesian reference system  $O_i x_i y_i z_i$ ,  $i=1\div 4$  and so the position vectors of mass center are void;

- Choosing the moving reference system so that their axes coincide with the main directions of inertial forces, associated with the origins of these systems, result that the mechanical centrifugal moments of inertia are void.

According to the Newton-Euler method, [6] and [7], first, the mechanical structure is walked by iteration to outward of the robot mechanical structure.

The mass distribution parameters are included in the table 1.

			Table 1
Element i	Mass M <sub>i</sub>	$\frac{\text{Mass}}{\text{centre}}$ $\overline{r}_{c_i}^i$	Inertial tensor $J_i^{\star i}$
1	$\mathbf{M}_1$		$\begin{bmatrix} J_x^{*1} & 0 & 0 \\ 0 & J_y^{*1} & 0 \\ 0 & 0 & J_z^{*1} \end{bmatrix}$
2	M <sub>2</sub>	$\begin{bmatrix} 0\\0\\0\end{bmatrix}$	$\begin{bmatrix} J_x^{*2} & 0 & 0 \\ 0 & J_y^{*2} & 0 \\ 0 & 0 & J_z^{*2} \end{bmatrix}$
3	M <sub>3</sub>	$\begin{bmatrix} 0\\0\\0\end{bmatrix}$	$\begin{bmatrix} J_x^{*3} & 0 & 0 \\ 0 & J_y^{*3} & 0 \\ 0 & 0 & J_z^{*3} \end{bmatrix}$
4	$M_4$		$\begin{bmatrix} J_x^{*4} & 0 & 0 \\ 0 & J_y^{*4} & 0 \\ 0 & 0 & J_z^{*4} \end{bmatrix}$

In table 1  $J_x^{*i}$ ,  $J_y^{*i}$ ,  $J_z^{*i}$ ,  $i=1\div 4$ , are the mechanical axial moments of inertia relative to the system i, with the origin in the mass center C<sub>i</sub>, and having the same guidance with the system attached to each element of the robot [1]. Next, are determining the accelerations corresponding to mass centers, with the following relations:

$$\overline{a}_{c_{1}}^{1} = \overline{a}_{1}^{1} + \overline{\varepsilon}_{1}^{1} \times \overline{r}_{c_{1}}^{1} + \overline{\omega}_{1}^{1} \times \left(\overline{\omega}_{1}^{1} \times \overline{r}_{c_{1}}^{1}\right), \begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{i}^{1} = \begin{bmatrix} \mathbf{0} \\ \ddot{g}_{1} \\ g \end{bmatrix}$$
(22)

Γο٦

$$\begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{3}^{3} = \begin{bmatrix} cq_{4} \cdot \ddot{q}_{2} + sq_{4} \cdot \ddot{q}_{1} \\ -sq_{4} \cdot \ddot{q}_{2} + cq_{4} \cdot \ddot{q}_{1} \\ g + \ddot{q}_{3} \end{bmatrix}$$
(24)  
$$\overline{a}_{c_{4}}^{4} = \overline{a}_{4}^{4} + \overline{\varepsilon}_{4}^{4} \times \overline{r}_{c_{4}}^{4} + \overline{\omega}_{4}^{4} \times \left(\overline{\omega}_{4}^{4} \times \overline{r}_{c_{4}}^{4}\right) \\ \begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{4}^{4} = \begin{bmatrix} cq_{4} \cdot \ddot{q}_{2} + sq_{4} \cdot \ddot{q}_{1} \\ -sq_{4} \cdot \ddot{q}_{2} + cq_{4} \cdot \ddot{q}_{1} \\ g + \ddot{q}_{3} \end{bmatrix}$$
(25)

According to [6], first, the mechanical structure is walked by iteration to outward of the robot mechanical structure. Thus, the reduction torsos elements for the external forces system, are determined, achieving the following relations:

$$\begin{bmatrix} \overline{F} \end{bmatrix}_{1}^{l} = M_{1} \begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{1}^{l}, \qquad \begin{bmatrix} M_{1} \cdot \ddot{q}_{1} \\ M_{1} \cdot g \end{bmatrix}$$
(26)

$$\overline{F}_{2}^{2} = M_{2}[\overline{a}_{c}]_{2}^{2}, \qquad [\overline{F}]_{2}^{2} = \begin{bmatrix} M_{2} \cdot \ddot{q}_{1} \\ M_{2} \cdot g \end{bmatrix}$$

$$[M_{c}(c\overline{a}, \ddot{a}_{c}) + c\overline{a}, \ddot{a}_{c})] \qquad (27)$$

$$\begin{bmatrix} \overline{F} \end{bmatrix}_{3}^{3} = M_{3} \begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{3}^{3}, \begin{bmatrix} \overline{F} \end{bmatrix}_{3}^{3} = \begin{bmatrix} M_{3} \cdot (cq_{4} \cdot q_{2} + sq_{4} \cdot q_{1}) \\ M_{4} \cdot (-sq_{4} \cdot \ddot{q}_{2} + cq_{4} \cdot \ddot{q}_{1}) \\ M_{3} \cdot (g + \ddot{q}_{3}) \end{bmatrix}$$
(28)  
$$\begin{bmatrix} \overline{F} \end{bmatrix}_{4}^{4} = M_{4} \begin{bmatrix} \overline{a}_{c} \end{bmatrix}_{4}^{4}, \begin{bmatrix} \overline{F} \end{bmatrix}_{4}^{4} = \begin{bmatrix} M_{4} \cdot (cq_{4} \cdot \ddot{q}_{2} + sq_{4} \cdot \ddot{q}_{1}) \\ M_{4} \cdot (-sq_{4} \cdot \ddot{q}_{2} + cq_{4} \cdot \ddot{q}_{1}) \\ M_{4} \cdot (g + \ddot{q}_{3}) \end{bmatrix}$$
(29)

## The moments of external forces are:

$$\overline{M}_{c_1}^1 = J_1^{*1} \overline{\varepsilon}_1^1 + \overline{\omega}_1^1 \times J_1^{*1} \overline{\omega}_1^1,$$

$$[\overline{M}_c]_1^1 = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^T,$$

$$\overline{M}_{c_2}^2 = J_2^{*2} \overline{\varepsilon}_2^2 + \overline{\omega}_2^2 \times J_2^{*2} \overline{\omega}_2^2,$$
(30)

$$\begin{bmatrix} \overline{M}_c \end{bmatrix}_2^2 = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^T$$

$$\overline{M}_{c_3}^3 = J_3^{*3} \overline{\varepsilon}_3^3 + \overline{\omega}_3^3 \times J_3^{*3} \overline{\omega}_3^3$$
,
(31)

$$\left[\overline{M}_{c}\right]_{3}^{3} = \begin{bmatrix} 0 & 0 & 0 \end{bmatrix}^{T}$$
(32)

$$\overline{M}_{c_4}^4 = J_4^{*4} \overline{\varepsilon}_4^4 + \overline{\omega}_4^4 \times J_4^{*4} \overline{\omega}_4^4$$

$$\left[\overline{M}_c\right]_4^4 = \begin{bmatrix} 0 & 0 & I_z^4 \cdot \overline{q}_4 \end{bmatrix}^T$$
(33)

In the second part of the Newton-Euler method, the mechanical structure is walked by iteration to inward of the robot mechanical structure.

$$F_{l_{5}}^{5} = \begin{bmatrix} F_{l_{x}}^{5} \\ F_{l_{y}}^{5} \\ F_{l_{z}}^{5} \end{bmatrix}; \qquad M_{O_{5}}^{5} = \begin{bmatrix} M_{x}^{5} \\ M_{y}^{5} \\ M_{z}^{5} \end{bmatrix}$$
(34)

Thus, the contact forces torsos between elements and their moments are determined, respectively the generalized driving forces from the robot's couplers. The reduction torsos elements of the payload handling are expressed by the relations (34).

According to relation (16), the contact forces have the following expressions:

$$\overline{F}_{l_{4}}^{4} = [R]_{5}^{4} \cdot \overline{F}_{l_{5}}^{5} + \overline{F}_{4}^{4}$$

$$[\overline{F}_{l}]_{4}^{4} = \begin{bmatrix} F_{l_{x}}^{5} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot sq_{4} \cdot \ddot{q}_{1} \\ F_{l_{y}}^{5} - M_{4} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{1} \\ F_{l_{z}}^{5} + M_{4} \cdot g + M_{4} \cdot \ddot{q}_{3} \end{bmatrix}$$
(35)

359



Fig. 2. The kinematics structure of the TTRT robot

(36)

$$\begin{split} \overline{F}_{l_{3}}^{3} &= \left[ R \right]_{4}^{3} \cdot \overline{F}_{l_{4}}^{4} + \overline{F}_{3}^{3} \\ & , \\ F_{l_{3}}^{5} &= \begin{bmatrix} F_{l_{x}}^{5} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot sq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot cq_{4} \cdot \ddot{q}_{2} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot cq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{1} - M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{3} \cdot cq_{4} \cdot \ddot{q}_{1} - M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{3} \cdot cq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{1} - M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot cq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} \cdot \ddot{q}_{2} + M_{4} \cdot \dot{q}_{3} + M_{3} \cdot sq_{4} - M_{3} \cdot sq_{4} \cdot \ddot{q}_{1} + M_{3} \cdot sq_{4} + M_{3} \cdot$$

$$\begin{split} \overline{F}_{l_2}^2 &= \left[ R \right]_3^2 \cdot \overline{F}_{l_3}^3 + \overline{F}_2^2 \\ \left[ \overline{F}_l \right]_2^2 &= \begin{bmatrix} F_{l_x}^5 \cdot cq_4 - F_{l_y}^5 \cdot sq_4 + M_4 \cdot \ddot{q}_2 \\ &+ M_3 \cdot \ddot{q}_2 + M_2 \cdot \ddot{q}_2 \\ &+ M_3 \cdot \ddot{q}_1 + M_4 \cdot \ddot{q}_1 + F_{l_y}^5 \cdot cq_4 \\ &+ M_3 \cdot \ddot{q}_1 + M_2 \cdot \ddot{q}_1 \\ &F_{l_z}^5 + M_4 \cdot g + M_4 \cdot \ddot{q}_3 + M_3 \cdot g \\ &+ M_3 \cdot \ddot{q}_3 + M_2 \cdot g \end{bmatrix} \end{split}$$

$$\overline{F}_{l_{1}}^{1} = [R]_{2}^{1} \cdot \overline{F}_{l_{2}}^{2} + \overline{F}_{1}^{1}$$

$$[\overline{F}_{l_{1}}]_{l}^{1} = \begin{bmatrix} F_{l_{x}}^{5} \cdot cq_{4} - F_{l_{y}}^{5} \cdot sq_{4} + M_{4} \cdot \ddot{q}_{2} + M_{4} \cdot \ddot{q}_{2} + M_{3} \cdot \ddot{q}_{2} + M_{2} \cdot \ddot{q}_{2} \\ F_{l_{z}}^{5} \cdot sq_{4} + M_{4} \cdot \ddot{q}_{1} + F_{l_{y}}^{5} \cdot cq_{4} + M_{3} \cdot \ddot{q}_{1} + M_{2} \cdot \ddot{q}_{1} + M_{1} \cdot \ddot{q}_{1} \\ F_{l_{z}}^{5} + M_{4} \cdot g + M_{4} \cdot \ddot{q}_{3} + M_{3} \cdot g + M_{3} \cdot \ddot{q}_{3} + M_{2} \cdot g + M_{1} \cdot g \end{bmatrix}$$

$$(38)$$

(38) The moments of contact forces have the expressions:

$$\overline{M}_{l_{0_{4}}}^{4} = [R]_{5}^{4} \cdot \overline{M}_{x}^{5} + \overline{r}_{c_{4}}^{4} \times \overline{F}_{4}^{4} + \overline{r}_{5}^{4} \times [R]_{5}^{4} \cdot \overline{F}_{l_{5}}^{5} + \overline{M}_{c_{4}}^{4},$$

$$[\overline{M}_{l}]_{0_{4}}^{4} = \begin{bmatrix} M_{l_{x}}^{5} - l_{3} \cdot F_{l_{y}}^{5} - l_{4} \cdot F_{l_{y}}^{5} - q_{3} \cdot F_{l_{y}}^{5} \\ M_{l_{y}}^{5} + l_{3} \cdot F_{l_{x}}^{5} + l_{4} \cdot F_{l_{x}}^{5} + q_{3} \cdot F_{l_{y}}^{5} \end{bmatrix}$$

$$M_{l_{2}}^{5} + J_{z}^{*4} \cdot \overline{q}_{3}$$

$$(37) \qquad \overline{M}_{l_{0_{3}}}^{3} = [R]_{4}^{3} \cdot \overline{M}_{l_{0_{4}}}^{4} + \overline{r}_{c_{3}}^{3} \times \overline{F}_{3}^{3} + \overline{r}_{4}^{3} \times [R]_{4}^{3} \cdot \overline{F}_{l_{4}}^{4} + \overline{M}_{c_{3}}^{3},$$

$$\begin{bmatrix} \overline{M}_{l_{v}}^{5} - l_{4} \cdot F_{l_{v}}^{5} - 2q_{3} \cdot F_{l_{v}}^{5} - q_{4} \cdot F_{l_{v}}^{5} + \\ q_{4} \cdot sq_{4} \cdot M_{4} \cdot \ddot{q}_{2} - q_{4} \cdot cq_{4} \cdot M_{4} \cdot \ddot{q}_{1} + \\ q_{4} \cdot sq_{4} \cdot M_{4} \cdot \ddot{q}_{2} + cq_{4} \cdot l_{5} \cdot M_{4} \cdot \ddot{q}_{1} + \\ q_{5} \cdot M_{4} \cdot sq_{4} \cdot \ddot{q}_{2} - cq_{4} \cdot q_{5} \cdot M_{4} \cdot \ddot{q}_{1} + \\ q_{5} \cdot M_{4} \cdot \ddot{q}_{2} + q_{5} \cdot sq_{4} \cdot M_{4} \cdot \ddot{q}_{1} - \\ cq_{4} \cdot l_{3} \cdot M_{4} \cdot \ddot{q}_{2} + q_{4} \cdot sq_{4} \cdot M_{4} \cdot \ddot{q}_{1} - \\ cq_{4} \cdot l_{3} \cdot M_{4} \cdot \ddot{q}_{2} + sq_{5} \cdot q_{4} \cdot M_{4} \cdot \ddot{q}_{1} - \\ cq_{4} \cdot l_{3} \cdot M_{4} \cdot \ddot{q}_{2} + sq_{5} \cdot q_{4} \cdot M_{4} \cdot \ddot{q}_{1} - \\ dq_{5} \cdot R_{1}^{2} - sq_{4} \cdot l_{5} \cdot F_{2}^{5} + sq_{4} \cdot M_{4} \cdot \ddot{q}_{1} - \\ cq_{4} \cdot q_{4} \cdot F_{1}^{5} - cq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3cq_{4} \cdot F_{2}^{5} \cdot q_{3} - \\ cq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3cq_{4} \cdot r_{5}^{5} - q_{4} \cdot d_{4} \cdot \ddot{q}_{1} - \\ 2q_{3} \cdot M_{4} \cdot \ddot{q}_{1} - l_{2} \cdot M_{4} \cdot \ddot{q}_{1} - l_{2} \cdot M_{3} \cdot \ddot{q}_{1} - \\ 2q_{3} \cdot M_{4} \cdot \ddot{q}_{1} - l_{2} \cdot M_{4} \cdot \ddot{q}_{1} - l_{2} \cdot M_{3} \cdot \ddot{q}_{1} - \\ 2q_{4} \cdot M_{5} \cdot f_{5} + cq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ cq_{4} \cdot M_{5} \cdot f_{5} + cq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ cq_{4} \cdot M_{5} \cdot f_{5} + cq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ cq_{4} \cdot M_{5} \cdot f_{5} + cq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} + sq_{4} \cdot l_{4} \cdot F_{1}^{5} - 3sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - sq_{4} \cdot q_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - sq_{4} \cdot q_{5} + \\ - \frac{l_{4} \cdot M_{5} \cdot f_{5}^{5} - cq_{4} \cdot l_{4} \cdot F_{1}^{5} - sq_{4} \cdot d_{5} \cdot F_{1}^{5} - \\ sq_{4} \cdot q_{4} \cdot F_{1}^{5} - sq_{4} \cdot l_{4} \cdot F_{1}^{5} - sq_{4} \cdot d_{5} \cdot F_{1}^{5} - \\ - sq_{4} \cdot q_{5} \cdot F_{1}^{5} -$$

$$\begin{split} M_{I_2} + J_2 \cdot \dot{q}_3 + J_2 \cdot \dot{q}_3 + sq_4 \cdot \dot{q}_2 \cdot F_{I_3} + \\ q_2 \cdot M_4 \cdot \ddot{q}_1 + q_2 \cdot M_3 \cdot \ddot{q}_1 + cq_4 \cdot q_2 \cdot F_{I_y}^5 + \\ q_2 \cdot M_2 \cdot \ddot{q}_1 \end{split}$$

(42)

The generalized driving forces are:

For axis 1 
$$O_1 y_1$$
, translation, the result is:  
 $Q_m^1 = sq_4 \cdot F_{l_x}^5 + M_4 \cdot \ddot{q}_1 + cq_4 F_{l_y}^5 + M_3 \cdot \ddot{q}_1 + M_2 \cdot \ddot{q}_1 + M_1 \cdot \ddot{q}_1$ 
(43)

For axis 2  $O_2 x_2$ , translation, the result is:  $Q_m^2 = cq_4 \cdot F_{l_x}^5 - sq_4 \cdot F_{l_y}^5 + M_4 \cdot \ddot{q}_4 + M_4 \cdot \ddot{q}_4 + M_4 \cdot \ddot{q}_4$ (44)

$$M_4 \cdot q_2 + M_3 \cdot q_2 + M_2 \cdot q_2 \tag{44}$$

For axis 3  $O_3 z_3$ , translation, the result is:  $Q_m^3 = F_{l_2}^5 + M_4 \cdot g + M_4 \cdot \ddot{q}_3 + M_3 \cdot g$  (45)

For axis 4  $O_4 z_4$ , rotation. the result is::  $Q_m^4 = M_{l_z}^5 + J_z^{x4} \cdot \ddot{q}_3$  (46)

#### **3. CONCLUSIONS**

To determine the robot's dynamic equations using the Newton-Euler method, is primarily needed the geometric and kinematics modeling. required Secondly are the distribution mass and certain simplifying parameters assumptions of choosing the mass centers C, but also the mechanical centrifugal moments of inertia. With these are determined the mass centers accelerations and the reduction torsor elements for the external forces.

The next step is to determine the torsos of the contact forces and the moments of these contact forces. The last step is to determine the driving generalized forces from the couplers robot, their expressions representing the dynamic equations of the TTRT robot.

These generalized driving forces represents the system of differential dynamic equations characterizing the dynamic model of serial modular TTRT robot.

#### **4. REFERENCES**

- Blebea. A.,V. Modelarea geometrica, cinematica si dinamica a unor roboti de tip Gantry, destinati aplicatiilor industriale. Raport de cercetare nr. 2, la teza de doctorat. Universitatea Tehnica din Cluj-Napoca, 2011.
- [2] Deteşan, O.A., Teză de doctorat: Cercetări privind modelarea, simularea şi construcția miniroboților. Universitatea Tehnica din Cluj-Napoca, 2007.

362

- [3] Fu, K., Gonzales, R., Lee, C, *Robotics, control, Sensing, Vision, and Intelligence.* McGraw-Hill International Editions, 1987.
- [4] Gui, Ramona-Maria, "Modelarea geometrică, cinematică şi dinamică a roboților industriali propuşi a fi impementați în fabricarea robotizată a reperelor de tip flanşă", Teza de doctorat, Universitatea Tehnica din Cluj-Napoca, 2011.
- [5] Ispas, V., *Aplicațiile cinematicii în construcția manipulatoarelor și a roboților industriali*, Editura Academiei Române, Bucuresti, 1990.
- [6] Ispas, V., Manipulatoare şi roboţi industriali, Editura Didactică şi Pedagogică, Bucureşti, 2004.
- [7] Negrean, I., Itul, T., Haiduc, N., "Cinematica roboților industriali", Centrul de multiplicare al Universității Tehnice, Cluj-Napoca, 1995.
- [8] Negrean, I., Duca, Adina, Negrean, C., Kacso, K., "Mecanică avansată în robotică", Editura U.T.PRESS, Cluj-Napoca, 2008.

# Elaborarea modelului dinamic pentru un robot modular Gantry, de tipul TTRT, cu ajutorul formalismului NEWTON EULER

**Rezumat**: În prima parte, lucrarea prezintă premisele teoretice necesare abordării problemei modelarii dinamice a unei structuri robotice seriale de tipul TTRT, folosind metoda Newton-Euler. În acest scop este nevoie în primul rând de modelarea geometrică și cinematică a structurii propuse iar în al doilea rând este necesară cunoașterea parametrilor de distribuție a maselor. Se fac anumite ipoteze simplificatoare legate de alegerea centrelor de masă. Deasemenea este necesară cunoașterea momentelor de inerție mecanice centrifugale a elementelor în mișcare de rotație. Pe baza acestor date s-a determinat în continuare accelerațiile corespunzătoare centrelor de masă, apoi elementele torsorului de reducere pentru sistemul forțelor exterioare, iar în continuare s-a determinat torsorul forțelor de legătură și cel al momentelor de legătură. Ultimul pas a fost determinarea forțelor generalizate motoare din cuplele robotului, expresiile acestora reprezentând ecuațiile dinamice ale structurii robotice seriale, de tipul TTRT. Studiul dinamic al unei structuri robotice seriale dă posibilitatea obținerii variantelor de combinare a modulelor pentru o structură optimizata, deasemenea dă posibilitatea alegerii legilor de mișcare pe fiecare axă cinematică, astfel încât consumul energetic, pe fiecare motor și pe întreaga structură, să fie minim.

- Adrian Vasile BLEBEA, Ph.D., Student. Dipl. Eng., Technical University of Cluj-Napoca, Department of Mechanical Engineering Systems, 103-105, Muncii Blvd., Office phone: 0264-401659.
- Viorel ISPAS, Ph.D., Dipl., Eng., Technical University of Cluj-Napoca, Department of Mechanical Engineering Systems, 103-105, Muncii Blvd., Office phone: 0264-401659.
- Radu Mircea MORARIU-GLIGOR Ph.D., Dipl., Eng., Technical University of Cluj-Napoca, Department of Mechanical Engineering Systems, 103-105, Muncii Blvd., Office Phone: 0264-401659.
- Iosif Nicuşor URSA Ph.D., Dipl., Eng., Technical University of Cluj-Napoca, Engineering Design and Robotics Department, 103-105, Muncii Blvd., Office Phone: 0264-401664.